



Dimensions	310mm x 310mm x 458mm (h)		12.2in x 12.2in x 18.03in (h)
Weight	19,7 kg		43,4 lb
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz
Current Consumption	2,1 A		3,6 A
Compressor Power	1/4 HP		
Power Consumption (Cooling)	315 W	1080 Btu/h	
Power Consumption (Heating)	400 W	1365 Btu/h	
Cooling Capacity *	630 W	2150 Btu/h	
Min and Max Water Flow	500 l/h - 800 l/h	132 Usgal/h - 211 Usgal/h	
Air Flow	160 m³/h	5650 CFH	
Maximum Exchanger's Pressure	0,6 bar	8,7 PSI	
Ambient Temperature Range	5°C - 38°C	41°F - 100°F	
Certification	CE		
Protection Grade	IPX4		

* the value reported refers to the following condition: room temperature 30°C (86°F), water temperature 25°C (77°F)

Material:	Drawing: TK 1000 – technical data		
Thickness:	File: TK_1000_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1: 5	Date: 09/04/2015
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	Drawer: Matteo		

AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ARCHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES. WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.

Modify:

Drawer: