



Dimensions	395mm x 600mm x 565mm (h)	15.55in x 23.62in x 22.24in (h)
Weight	47kg	103,7 lb
Voltage-Frequency	115V -60Hz	
Current Consumption	11,2A	
Compressor Power	1 1/2 HP	
Power Consumption (Cooling)	1200 W	
Power Consumption (Heating)	1200 W	
Cooling Capacity *	3070 W	10480 Btu/h
Min and Max Water Flow	3000 l/h - 4000 l/h	793 Usgal/h - 1057 Usgal/h
Air Flow	450 m³/h	15900 CFH
Maximum Exchanger's Pressure	1 bar	14,5 PSI
Ambient Temperature Range	5°C - 38°C	41°F - 100°F
Certification \ Protection Grade	CE \ IPX4	
Gas Type and Quantity	R410A \ 800 g	
* the value reported refers to the following condition: room temperature 30°C (86°F), w ater temperature 25°C (77°F)		
** All data may be changed w ithout notice by TECO		
*** Reported values are approximate - other details on request		

"H" model: - 3 x Heater kit - 1 x UV-C kit	Material:	Drawing: TK9000/TK9000H – technical data	
	Thickness:	File: TK9000_TK9000H_technical_drawing	
Approved:	Finishing:	Your.code:	Code:
	Volume:	Tol.	Scale: 1:10 Date: 07/11/2016
 Drawer: Giulia	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	<small>AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ACHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES.WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.</small>		

Drawer: Modify