



Dimensions	816mm x 690mm x 1050m (h)	32.13in x 27.17in x 41,34in (h)
Weight	130 kg	287 lb
Voltage-Frequency-Phase	400V - 50Hz - 3ph	230V - 60Hz - 3ph
Current Consumption	11,5 A	15,2
Compressor Power	6 HP	
Power Consumption (Cooling)	6890 W	23500 Btu/h
Power Consumption (Heating)	4100 W	14000 Btu/h
Cooling Capacity*	15 KW	511800 Btu/h
Min and Max Water Flow	6500 l/h - 8000 l/h	1717Usgal/h - 2113 Usgal/h
Air Flow	7000 m ³ /h	247200 CFH
Maximum Exchanger's Pressure	2 bar	29 PSI
Ambient Temperature Range	5°C - 38°C	41°F - 100°F
Certification	CE	
Protection Grade	IPX4	
* the value reported is approximate. Other details on request		

Material:	Drawing: TK 15K – Technical data		
Thickness:	File: TK_15K_technical_drawing		
Finishing:	Your.code:	Code:	
Volume:	Tol.	Scale: 1:15	Date: 06/07/2015
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	Drawer: Matteo		