



Dimensions	816mm x 690mm x 850m (h)	32.13in x 27.17in x 33.46in (h)
Weight	105 kg	232 lb
Voltage-Frequency-Phase	400V - 50Hz - 3ph	230V - 60Hz - 1ph
Current Consumption	7,6 A	13,1
Compressor Power	4 HP	
Power Consumption (Cooling)	4350 W	14850 Btu/h
Power Consumption (Heating)	2800 W	9550 Btu/h
Cooling Capacity*	8 KW	27300 Btu/h
Min and Max Water Flow	4500 l/h - 6000 l/h	1189 Usgal/h - 1585 Usgal/h
Air Flow	7000 m <sup>3</sup> /h	247200 CFH
Maximum Exchanger's Pressure	2 bar	29 PSI
Ambient Temperature Range	5°C - 38°C	41°F - 100°F
Certification	CE	
Protection Grade	IPX4	

\* the value reported is approximate. Other details on request

Material:	Drawing: TK8K - technical data		
Thickness:	File: TK_8K_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1:15	Date: 14/04/2016
Approved:	Via A.Sansovino, 35 48124 RAVENNA - ITALY Tel. +39 0544 408333 Fax 280084 <a href="http://www.tecoonline.com">http://www.tecoonline.com</a>		
	Drawer: Matteo		